



MilchMobil NEXT

**MilchMobil 120Liter
(push)**



**MilchMobil 200 Liter
(follower)**



**MilchMobil 300 Liter
(follower)**



■ Wide

■ Fits through any common door

- 120 L: narrower like MDK4 68 cm
- 200/300 L same as MDK4 79 cm (like MDK4)

■ Filling height

■ 200 liters not higher than 120 liters

- 120/200 L **102 cm (approx. 10 cm higher than MDK4)**
- 300 L **127 cm**



Functions that convince



Drawbar (push)
Function keys for dosing pump, feeding quantities and drive level



Control panel:

- Intuitive operation via symbols
- Direct keys for quick access to functions



Water bath heating :

- Gentle heating of the milk
- No burning
- Keep warm function during feeding

Robust, Stable – MilchMobil



Drawbar (follower):

- Height adjustable between 94 - 106 cm
- Function keys for dosing pump, feeding quantities and drive level



Dosing gun:

- Integrated button for dispensing
- Holder for convenient storage at working height



Discharge taps:

- Easy emptying of milk tank and dosing hose



4 wheels and axle steering

- Good off-road capability
- High driving stability



Dosing arm (option):

- Attachment of the dosing gun for convenient dosing out
- Height adjustable
- Swiveling



Portion control

- Up to five portion sizes programmable
- PUSH function for unlimited dosing
- Dosing out via function keys or pushbuttons on the dosing arm



Cyclone cleaning

- Rotating cleaning nozzle for tank cleaning
- Quick-release fastener for easy changing of the cleaning nozzle
- Functions according to the dishwasher principle



LLED:

- 360° rotatable
- Illumination of the boxes and the driving path



Mixer and stirrer:

- Mixing of MP-feed
- Stirrer function for milk feeding
- Control also possible while driving and feeding



Heating control:

- Timers, automatically combinable
- for up to three feeding times
- Frost protection function



Can holder (option):

- Facilitates the transport of buckets or cans
- foldable

Pasteurization of milk

- 200l and 300l model
- Automatic process cycle
 - Heating up, holding (63° 35min) and cooling down
- Cooling through coat and bottom
 - Faster cooling function
 - Small volumes possible
 - AMS function included



■ AMS* equipment

- **Cooling of small quantities** during filling by the milking robot throughout the day
- High forage quality even at higher outside temperatures

NEW

■ Fresh milk feeding

- **Slow and fast running stirrer / mixer**
 - Intensive mixing of MP and gentle stirring of fresh milk
 - **Automatic** speed switching during heating (slow) and cleaning
 - Control also during driving and feeding

NEW



- Pullable and pushable models
 - The right solution for every user
 - 120 liter push cart (pushable)
 - 200 / 300 liter walk-behinds (pullable)

- Angled mixer
 - Intensive stirring of Milk replacer or additives
 - Good visibility into the tank

NEW

NEW



- Water bath
 - Gentle heating
 - No burning of the potions
 - **Fast heating (automatic preheating function)**
 - Keep warm function during transport
- Intensive cleaning
 - Cleaning nozzle based on the dishwasher principle (cyclone cleaning)
- 4 wheels
 - high driving stability and good driving characteristics in any terrain

NEW



■ Cost-effective **plan-controlled feeding**

- **No** cost-intensive identification and tags for animal identification necessary
- Comparable to the CalfRail system that has been proven for years
 - Box number corresponds to animal number

NEW

■ Electrical energy saving

- Heating of the feeding with AMS units by available hot water
 - Via cooling and heating floor

NEW



MilchMobil NEXT - Clean & Fill Station



- Quick and easy connection to the station
- Fully automatic cleaning of the MilchMobil Next
- Fully automatic filling and heating of water for next feeding



INNOVATION
AWARD

EuroTier

SILVER MEDAL



Automatically also with MilchMobil!